





75 SERIES
75cm presses

75IVH four colour • 75IVHP four colour perfector
75VH five colour • 75VHP five colour perfector
75VIH six colour • 75VIHP six colour perfector
75VIIIH eight colour • 75VIIIHP eight colour perfector

With high pile delivery

Running Speed	4,000 - 17000 SPH			
Max Sheet Size	520 x 750 mm			
Min Sheet Size	(Single-sided) 200 x 296 mm (Perfecting) 300 x 400mm			
Max Printing Area	(Single-sided) 510 x 740 mm (Perfecting) 500 x 740 mm			
Plate Size	605 x 745 or 754 x 0.24 or 0.3 mm			
Stock range	0.04 to 0.4 mm			
Feeder Pile Height	900 mm			
Delivery Pile Height	730 mm			
Blanket Size (W x L x T)	765 x 780 x 1.95 mm			
Inking Roller	20 per unit			
Dampening System	Continuous Dampening System			
Dampening Roller	5 per unit			
Feeder System	Stream Feeder			
Delivery system	7 Gripper Bars with High-Pile Delivery			

	92 _H	79 _H	75н	66н	<i>52</i>
Feeder Pile Paper Preloading Device	•	•	•	•	•
Mechanical Double Sheet Detector		•	•	•	•
Electrical Double Sheet Detector	•	•	•	•	0
On-the-Run Feeder Timing Adjustment		•	•	•	•
Impression On/Off Detector		•	•	•	•
Overrun Sheet Detector		•	•	•	•
Side Guide Paper Detector		•	•	•	0
Antistatic Blower on Feeder Head		0	0	0	0
Remote Controlled Ink Key Adjustment		•	•	•	•
Dampening Fountain Roller Speed Remote Control System		•	•	•	•
Free Standing Dampening Cooling/Circulating Unit		•	•	•	•
Continuous Dampening System	•	•	•	•	•
Segmented Ink Fountain Blade		•	•	•	•
Ink Roller Wash up Blade/Tray		•	•	•	•
Dampening Solution PH Controller	•	•	•	•	•
Automatic Alcohol (IPA)% Controller	•	•	•	•	•
Hickey Picker Device	•	•	•	•	•
Automatic Ink Roller Wash up System	•	•	•	•	0
Oscillating Ink Form chilling Roller	0	0	0	0	
Temperature Controlled Printing System (TCPS)	0	0	0	0	
Oscillating Ink Form Roller (Anti-ghosting Roller)	0	0	0	0	0
Plate Cylinder Lateral/Radial Remote Control Device					•
SPC (Shinohara Plate Changer)Semi automatic					
Automatic Blanket Wash up System					
Cloth Type Automatic Blanket Wash up System	0	0	0	0	0
Operation Side Impression Adjustment Dial		•	•	•	
Impression Pressure Pre-set System					
Anti-Smearing Paper on Transfer Cylinder					
Delivery Missing Sheet Detector					
Plate Clamp Cocking System					
Plate Cylinder Cocking System					
Automatic Impression Cylinder Wash up System	0	0	0	0	
Sheet Decurler	•		•	•	
Static Eliminator			•		
Spray Powder System					
Spray Powder Replenisher					
Sheet Brake		•	•	•	
Faulty Delivered Sheet Detector		•	•	•	
Tab Inserter	•	_		0	0
Nonstop Delivery	•	0	•	•	J
Swing-away Unit (Imprinting and Numbering)					0
Radial Perforating Device					0
Longer Delivery	0	0		0	J
		0	0	0	
Aqueous Inline Coater	0	0	0		
UV & Aqueous Inline Coater Infrared Dryer Device	0	0	0	0	^
•	0	0	0	0	0
UV Curing Device	0	0	0	0	
Interdeck UV Curing Device	0	0	0	0	
POD Touch Screen		•	•	•	•
Total Counter		•	•	•	•
Preset Sheet Counter	•	•	•	•	•
Plate Puncher	0	0	0	0	0
Paper Size Pre-set System	•	0	0	0	
Operation Console		•	•	•	•
Shinohara CIP3 Station	•	•	•	•	•
Shinohara Pre-Inking System (SPIS)	•	•	•	•	•
Shinohara Color Control Station(SCCS)	0	0	0	0	0



● Standard O Option